



Wyse V90LE

Maximum Flexibility and Power for Thin Computing

The high-range Wyse V90LE thin computer delivers the Windows XPe performance you need; dual-video support (with purchase of optional monitor splitter cable); a CardBus/PCMCIA slot; plus serial, parallel, and USB ports. Using the same form-factor as the Wyse V class family of thin computers, the Wyse V90LE thin computer can fit easily into most work environments.

Features	Benefits
Microsoft Windows XPe SP2 Wyse Feature Release 1 (WFR1)	Rich Windows desktop environment to run desktop application software with vast peripheral and device driver support, plus the ability to embed local applications.
Runs familiar Windows XP graphical user interface with Wyse firmware enhancements	Wyse enhancements include security features, optional windowing, fast boot, and more.
Local Windows XP interface, also displays desktops and applications via multiuser Windows NT and 2000 servers	Delivers high availability of key applications because they can run either on the server or locally.
Enables embedding of customer-selected local 32-bit Windows applications	Delivers the flexibility, performance, and power of the Windows operating system.
Supports RDP 6.x, ICA 10.x, and SGD 4.x protocols with 15 resident terminal emulation options	Connectivity to almost any back-end system and flexibility to choose the optimal protocol
Support for latest Citrix ICA client (version 10.x), including digital dictation for ICA	Allows you to use Progressive Speedscreen acceleration, Optimized for Citrix Presentation Server 4.5, Enhanced Proxy Detection support, support for Advanced Encryption Standard (AES), Trusted Server Configuration

Technical Specifications

Processor	Via C7 Eden 1.2GHz
Memory	512MB Flash/256MB DDR2 RAM Other configurations (up to 2GB/1GB) available
I/O peripheral support	<ul style="list-style-type: none"> - One DVI-I Port - One DVI-I Port to VGA (DB-15) Adapter - Dual-video Support with: Optional DVI-I to DVI-D plus VGA-monitor splitter cable (sold separately) - Enhanced USB keyboard with PS/2 mouse port and Windows keys - PS/2 mouse included - One serial port - One parallel port - Three USB 2.0 ports (1 on front, 2 on back)
Networking	10/100 Base-T Fast Ethernet twisted pair (RJ-45) Optional external USB 802.11b/g wireless adapter
Display	<ul style="list-style-type: none"> - VESA monitor support with Display Data Control (DDC) for automatic setting of resolution and refresh rate - Single Monitor at 32-bit color: up to 1600x1200@85Hz up to 1920x1080@60Hz - Dual Monitors used simultaneously (requires optional monitor splitter cable) at 32-bit color: up to 1920x1080@60Hz
Audio	Output: 1/8-inch mini, full 16-bit stereo, 48KHz sample rate Input: 1/8-inch, 8-bit mini microphone
Options	Internal Smart Card reader Internal wireless CardBus/PCMCIA card slot
Physical characteristics	Height: 7.9 inches (201mm) Width: 1.8 inches (46mm) Depth: 7.1 inches (180mm) Shipping Weight: 8 lbs. (3.6kg)
Mountings	Vertical foot (optional horizontal feet) Optional VESA mounting bracket Built-in Kensington security slot (cable sold separately)
Power	Worldwide auto-sensing 100-240 VAC, 50/60 Hz Average power usage with device connected to 1 keyboard with 1 PS/2 mouse and 1 monitor: 17.2 Watts/hour
Temperature Range	Horizontal position: 50° to 95° F (10° to 35° C) Vertical position: 50° to 104° F (10° to 40° C)
Security	Kensington Lock Slot
Safety Certifications	German EKI-ITB 2000, ISO 9241-3/-8 cULus 60950, TÜV-GS, EN 60950 FCC Class B, CE, VCCI, C-Tick WEEE, RoHS Compliant
Warranty	Three-year limited warranty



Wyse Technology Inc.
3471 North First Street
San Jose, CA 95134-1801

Visit our website at:
<http://www.wyse.com>

Or send email to:
sales@wyse.com

Wyse Sales:
800 GET WYSE
(800 438 9973)

Wyse Customer
Service Center:
800 800 WYSE
(800 800 9973)